DICKSTEIN, SHAPIRO, MORIN & OSHINSKY LLP
Ziol I. Street NW
Washington DC 20037-1526

PAY ***Six Hundred Ninety and \$0/190 Pollers***

TO Federal Communications
Commission

To General Communications
Commission

To Co

#054001204#470398 7M

*000006 90000 A

#153230#

Federal Communications Commission Washington, D. C. 20554

Approved by 3060 Expires 06

OMB	
-0027	
30/98	

FOR FCC USE ONLY M. Maria

MAN

FCC 301

APPLICATION FOR CONSTRUCTION **PERMIT**

FOR COMMERCIAL BROADCAST STATION

FOR COMMISSION USE ONLY	
FOR COMMISSION OSF, ONLY	
FILE NO. 1/80309-JE	`

ORIGINAL

Section I - GENERAL INFORMATION			
APPLICANT NAME (Last, First, Middle Initial)	(Mar.) Martines () () () () () () () () () (10
DOGWOOD COMMUNICATIONS, INC.			
MAILING ADDRESS (Line 1) (Maximum 35 characters) c/o Neal J. Friedman, Esq.			
MAILING ADDRESS (Line 2) (Maximum 35 characters) 2101 L Street, N.W.			
CITY Washington	STATE OR COUNTRY D.C.	(if foreign address)	ZIP CODE 20037-1526
TELEPHONE NUMBER (include area code) 202-833-7025	CALL LETTÉRS WAMJ (FM)	OTHER FCC ID	ENTIFIER (IF APPLICABLE
2. A. Is a fee submitted with this application?			X Yes No
B If No, indicate reason for fee exemption (see 47 C.F.R.	Section 1.1113) and go	to Question 3	
Governmental Entity Noncommercial e	ducational licensee	Other (Please exp	olain):
C. If Yes, provide the following information:			
Enter in Column (A) the correct Fee Type Code for the se "Mass Media Services Fee Filing Guide." Column (B) list (C) the result obtained from multiplying the value of the Fee	s the Fee Multiple appli	cable for this appl	ication. Enter in Column
(A) (B)	(C)		
FEE TYPE CODE FEE MULTIPLE (if required)	FEE DUE FOR FE CODE IN COLUI	4	FOR FCC USE
M P R 0 0 0 1	\$ 690		6-90.00
To be used only when you are requesting concurrent actions	which result in a require	ment to list more t	han one Fee Type Code.
(A) (B)	\$		FOR FCC USE ONLY
ADD ALL AMOUNTS SHOWN IN COLUMN C, LINES (1) FHROUGH (2). AND ENTER THE TOTAL HERE. FHIS AMOUNT SHOULD EQUAL YOUR ENCLOSED REMITTANCE	TOTAL AMOU REMITTED WIT APPLICATIO \$ 690	THIS	FOR FCC USE ONLY

107.5MHZ

- 980309IE SPH

WAMJ

ROSWELL

GA

Section I - GENERAL INFORMATION (Page 2) \mathbf{x}_{FM} \square_{TV} \rfloor_{AM} 3. This application is for: (check one box) (b) Channel No. or Frequency State City (b) Principal 298C3 Roswell Georgia Community (c) Check one of the following boxes: Application for NEW station MAJOR change in licensed facilities; call sign: WAMJ (FM) MINOR change in licensed facilities; call sign: MAJOR modification of construction permit; call sign: File No. of construction permit; call sign:

NOTE: It is not necessary to use this form to amend a previously filed application. Should you do so, however, please submit only Section I and those other portions of the form that contain the amended information.

AMENDMENT to pending application: Application File Number:

MINOR modification of construction permit; call sign:

File No. of construction permit; call sign:

4. Is this application mutually exclusive with a renewal application?

Call letters	Community of License	
Cun lotters	City	State

Yes X No

If Yes, state:

301 921-0115 Voice 301 590-9757 Fax mullengr@aol.com E-mail

MULLANEY ENGINEERING, INC.

9049 SHADY GROVE COURT GAITHERSBURG, MD 20877

ENGINEERING EXHIBIT EE-3:

RADIO STATION WAMJ
DOGWOOD COMMUNICATIONS, INC.
ROSWELL, GEORGIA
Ch. 298C3 9.2 KW-DA 163 M HAAT

MARCH 5, 1998

ENGINEERING STATEMENT IN SUPPORT OF

AN APPLICATION FOR A

"ONE-STEP" UPGRADE

ORIGINAL SIGNATURE

ENGINEERING EXHIBIT EE-3:

RADIO STATION WAMJ DOGWOOD COMMUNICATIONS, INC. ROSWELL, GEORGIA Ch. 298C3 9.2 KW-DA 163 M HAAT

TABLE OF CONTENTS:

- 1. F.C.C. Form 301, Section V-B.
- 2. Declaration of Engineer.
- 3. Narrative Statement.
- 4. Figure 1, Topographic Map Showing Proposed Site. (not required)
- 5. Figure 2, Map Showing Proposed Contours.
- 6. Figure 2-A, Tabulation of Proposed Contours.
- 7. Figure 2-B, Map Showing City Grade Contour.
- 8. Figure 3, Vertical Tower Sketch.
- 9. Figure 4, C3 Channel Allocation Proposed Site.
- 10. Figure 5, Short Spacing Allocation Map.
- 11. Figure 5-A, WAMJ Short Spacing Contours.
- 12. Figure 5-B, WCGQ Short Spacing Contours.
- 13. Figure 6, Horizontal Radiation Pattern Relative Field.
- 14. Figure 6-A, Tabulation of Horizontal Radiation Pattern.
- 15. Figure 7, FM Antenna Elevation Pattern.
- 16. Figure 7-A, RF Exposure Analysis.
- 17. Figure 8, C3 Channel Allocation Special Reference Site.
- 18. Figure 8-A, Topographic Map Showing Special Reference Site.

SECTION V-B	3 - FM BROADCAST	ENGINEERIN		FOR COMMISSION File No. SSB Referral Date Referred By	N USE ONLY				
Name of Applic	eant Dogwood Commu	nications	. Inc.						
Call Letters (if				eing filed in re	sponse to a window?)	Yes	X N	
WAM	J	If Yes	ng date:						
	olication: (check appropriate	priate boxes)							
Cons	struct a new (main) fac	cility		Cor	struct a new auxilia	y facility			
Mod	lify existing construction	on permit for ma	ain facility	□ Мо	dify existing constru	ction permit fo	or auxiliary	facility	
Modify licensed main facility					dify licensed auxiliar	y facility			
If purpose is to	modify, indicate below	w the nature of c	change(s) and	specify the file	number(s) of the aut	horizations af	fected.		
	enna supporting struct		_		ective radiated power				
	enna height above ave			Fre	quency				
	enna location	C		Cla					
	Main Studio location				One-Step processing				
	ectional Antenna				ner (summarize) MX	with RM	i		
_	umber(s) Class_A	license	is pendi	_	(04				
I. Allocation									
Channel No.	P	rincipal commu			Class	(check only o	one box belo	ow)	
	County	City or T	own	State		L	В		
298	Fulton	Ros	well	G.F		22 ∐ C1	$\bigcup C$		
(a) Spec Tov (b) Geog Othe	ation of antenna. Sify address, city, count wer Place, 33 graphical coordinates erwise, specify tower 1 t Longitude will be pre	340 Peacht (to nearest seco ocation. Specify	tree Rd., nd). If mounted South Latitud	Atlanta ed on element de and East Lo	a, GA (Fulto of an AM array, spennitude where applications	n Co.) cify coordinat cable; otherwi	es of cente	r of ar	
Latitude	33°	50'	48"	Longitude	84°	22 '		16"	
3. Is the su application	apporting structure thon(s)?	e same as that	of another s	station(s) or p	roposed in another	pending	Yes		
If Yes, gi	ve call letter(s) or file	number(s) or bo	th. KNKO8	29, KEF9	46, WPGI484				
• •	al involves a change in ourtenances, and lighting	_	isting structur	e, specify exist	ing height above gro	und level incl	uding anten	ına, all	

Section V-B - FM BROADCAST ENGINEERING DATA (Page 2)

4.			oplication propose to old coordinates.	o correct previo	ous site coordinate	es?		Yes	No
Lat	itude		0	1	11	Longitude	0	ı	ŧŧ
5.			A been notified of t					FIRM	No I
							ibit a copy of FAA Increase in		
	Date	e		C	Office where filed_		***************************************		
6.	List runv		ding areas within 8	km of antenna	a site. Specify dista	ance and bearing	ng from structure to i	nearest point of the neares	st
	(a)		Landing Area E Kalb - Pea	achtree	Dist	tance (km)		Bearing (degrees True) 68.	
	(b)								
7.	(a)	Eleva	ntion (to the nearest	meter)					
		(1)	of site above mean	sea level;				301.8 m	eters
		(2)	of the top of suppo-				a, all other on building	<u>162.2</u> m	eters
		(3)	of the top of suppo					463.9 _m	eters
	(b)		ht of radiation center						
	(0)	(1)	above ground;	(10 110 110111		. izoiiui,		146. m	eters (
		(.,	acovo ground,					146. m	eters (
		(2)	above mean sea le	vel [(a)(1) + (b)(1)]: and			448. m	
		(2)	uoovo moun sou le	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,)(1)], and			448. m	,
		(3)	above average teri	rain.				163. m	eters (
								163. m	eters (
8.	Que	estion		m 7(b)(3). If n	nounted on an Al	M directional a	levations required in rray element, specifior.		
9.	Eff	ective l	Radiated Power:						
	(a)	ERP	in the horizontal p	lane	9.2 kw (H*)	9.2 kw (V*)		
		Is be	eam tilt proposed?					Yes	No
			es, specify maximu ical elevation plot o	f radiated field	•		ttach as an Exhibit	a Exhibit No.	
		Pol	larization		kw (H)	kw (V*)		

Section V-B - FM BROADCAST ENGINEERING DATA (Page 3)

10.	Does	this proposal modify	a new unbuilt constr	ruction permit fo	r an unbuilt, unlic	ensed facility?	Yes	No
	a cert	s, submit an Exhibit of ification that construction.					Exhibit N	No.
11.	Is a d	irectional antenna pr	oposed?				Yes	☐ No
		s, attach as an Exhibit s), and tabulations of		data specified in	47 C.F.R. Section	73.316, including	Exhibit! Fig 6	No. ,6A
12.	Will	the proposed facility	satisfy the requireme	ents of 47 C.F.R.	Section 73.315(a)	and (b)?	Yes	☐ No
	If No, attach as an Exhibit a request for waiver and justification therefor, including amounts and percentages of population and area that will not receive 3.16 mV/m service.							No.
13.	Will	the main studio be w	ithin the protected 3	.16 mV/m field s	strength contour of	f this proposal?	Yes	☐ No
	If No, attach as an Exhibit justification pursuant to 47 C.F.R. Section 73.1125.							No.
14.		is application being fi 59, 8 FCC 2d 4735 (i			o the Report & Orc	ler in MM Docket	Yes	No
		his muse comedime (1)		e is in compliance		and a Calling A month of		
	Exhi 1985 exist Secti separ site i	bit must contain: (1) 5, Public Notice, Mir- ing tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower of coordinates for the p	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7. construction.	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) a s	with the requireme flotment site will site is in complian and site meets the m	be located on an ace with 47 C.F.R. minimum distance		
La	Exhi 1985 exist Secti separ site i	5, Public Notice, Mining tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower of the su	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7. construction.	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) a s	with the requireme flotment site will site is in complian and site meets the m	be located on an ace with 47 C.F.R. minimum distance	21'	06"
L	Exhi 1985 exist Secti sepa site i	5, Public Notice, Mining tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower coordinates for the p	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7 construction.	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) a stee are:	with the requireme llotment site will site is in compliar nt site meets the natatement that the p	be located on an ace with 47 C.F.R. minimum distance roposed allotment	21 ' Yes	06" ■ No
L	Exhi 1985 exist Secti sepa site i The	5, Public Notice, Mincing tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower coordinates for the p	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7 construction.	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) a stee are: 11"	with the requireme flotment site will site is in compliar nt site meets the natatement that the part Longitude C.F.R. Section 73	be located on an ace with 47 C.F.R. minimum distance roposed allotment	Yes	No No
L	Exhi 1985 exist Secti sepa site i The	5, Public Notice, Mining tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower of coordinates for the p 33° Does the proposed for the answer to (a)	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7 construction. roposed allotment si	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) as te are: 11" quirements of 47	with the requireme flotment site will site is in compliar nt site meets the natatement that the purpose Longitude C.F.R. Section 73 apply?	be located on an ace with 47 C.F.R. minimum distance roposed allotment 84° 207? Fig 4	Yes	No No
L	Exhi 1985 exist Secti separ site i The titude (a)	5, Public Notice, Mining tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower coordinates for the p 33° Does the proposed for the answer to (a) if the answer to (b) i waivers.	an allotment site ma meo 3693, or a state coverage map, showi wing demonstrating f 47 C.F.R. Section 7 construction. roposed allotment si	p that complies we ment that the ang the allotment that the allotme that the allotme 3.207; and (4) a set to are: 11" Quirements of 47 A. Section 73.213 Ahibit a justification (b) is No, attack	vith the requireme llotment site will site is in compliar nt site meets the ntatement that the p Longitude C.F.R. Section 73 apply? on, including a sur	be located on an acce with 47 C.F.R. minimum distance proposed allotment 84° 207? Fig 4	Yes	No No No.
L	Exhi 1985 exist Secti separ site i The titude (a) (b) (c)	5, Public Notice, Mining tower; (2) a city of ion 73.315; (3) a sho ration requirements of is suitable for tower of coordinates for the parameter of the proposed for the answer to (a). If the answer to (b) is waivers. If the answer to (a) is the short spacing(s)	an allotment site maneo 3693, or a state coverage map, showing demonstrating f 47 C.F.R. Section 7 construction. Toposed allotment si 59 Cacility satisfy the receis No, does 47 C.F.R. s Yes, attach as an Expression of the construction of the construction.	p that complies we ment that the ang the allotment that the allotme 3.207; and (4) a set are: 11" quirements of 47 a. Section 73.213 shibit a justification (b) is No, attackarose.	Longitude C.F.R. Section 73 apply? on, including a sure as an Exhibit a sta	be located on an acce with 47 C.F.R. minimum distance proposed allotment 84° 207? Fig 4	Yes Yes Exhibit	No No No.

Section V-B - FM BROADCAST ENGINEERING DATA (Page 4)

- (1) Protected and interfering contours, in all directions (360°), for the proposed operation.
- (2) Protected and interfering contours, over pertinent arcs, of all short-spaced assignments, applications and allotments, including a plot showing each transmitter location, with identifying call letters or file numbers, and indication of whether facility is operating or proposed. For vacant allotments, use the reference coordinates as the transmitter location.
- (3) When necessary to show more detail, an additional allocation study utilizing a map with a larger scale to clearly show prohibited overlap will not occur.
- (4) A scale of kilometers and properly labeled longitude and latitude lines, shown across the entire Exhibit(s). Sufficient lines should be shown so that the location of the sites may be verified.
- (5) The official title(s) of the map(s) used in the Exhibit(s).
- 16. Are there: (a) within 60 meters of the proposed antenna, any proposed or authorized FM or TV transmitters, or any nonbroadcast (except citizens band and amateur) radio stations; or (b) within the blanketing contour, any established commercial or government receiving stations, cable head-end facilities, or populated areas; or (c) within ten (10) kilometers of the proposed antenna, any proposed or authorized FM or TV transmitters which may produce receiver-induced intermodulation interference?

If Yes, attach as an Exhibit a description of any expected, undesired effects of operations and remedial steps to be pursued if necessary, and a statement accepting full responsibility for the elimination of any objectionable interference (including that caused by receiver-induced or other types of modulation) to facilities in existence or authorized or to radio receivers in use prior to grant of this application. (See 47 C.F.R. Sections 73.315(b), 73.316(e) and 73.318.)

- 17. Attach as an Exhibit a 7.5 minute series U.S. Geological Survey topographic quadrangle map that shows clearly, legibly, and accurately, the location of the proposed transmitting antenna. This map must comply with the requirements set forth in Instruction V (D). The map must further clearly and legibly display the original printed contour lines and data as well as latitude and longitude markings, and must bear a scale of distance in kilometers. Existing Communications Site
- 18. Attach as an Exhibit (name the source) a map which shows clearly, legibly, and accurately, and with the original printed latitude and longitude markings and a scale of distance in kilometers:
 - (a) the proposed transmitter location, and the radials along which profile graphs have been prepared;
 - (b) the 3.16 mV/m and 1 mV/m predicted contours; and
 - (c) the legal boundaries of the principal community to be served.
- 19. Specify area in square kilometers (1 sq. mi. = 2.59 sq. km.) and population (latest census) within the predicted 1 mV/m contour.

Area 4,352 sq. km.

Population 2,195,992

1990 Census

20. For an application involving an auxiliary facility only, attach as an Exhibit a map (Sectional Aeronautical Chart or equivalent) that shows clearly, legibly, and accurately, and with latitude and longitude markings and a scale of distance in kilometers:

Exhibit No.

Yes

Exhibit No.

EE-3

Exhibit No.

Exhibit No.

Fig 2,A,B

N/A

☐ No

- (a) the proposed auxiliary 1 mV/m contour; and
- (b) the 1 mV/m contour of the licensed main facility for which the applied-for facility will be auxiliary. Also specify the file number of the license.

Section V-B - FM BROADCAST ENGINEERING DATA (Page 5)

Date

March 5, 1998

21. Terrain and coverage data (to be calculated in accordance with 47 C.F.R. Section 73.313)

Linearly inte	rpolated 30-second database	7.5 minute topographic	map
(Source: NG	DC)	
Linearly inte	rpolated 3-second database	Other (summarize)	
Radial bearing	Height of radiation center above average	Predicted D	istances
(degrees True)	elevation of radial from 3 to 16 km (meters)	To the 3.16 mV/m contour (kilometers)	To the 1 mV/m contour (kilometers)
*			
0 City	152.8	22.4	38.0
45	148.3	22.0	37.3
90	153.5	22.4	38.0
135	159.7	22.9	38.6
180	163.1	19.3	32.8
225	181.4	19.0	32.3
270	179.0	24.0	40.7
315	162.7	23.0	39.1
22. Environmental State Would a Commission may have a significate to levels of RF radia National Standards		req.) 47 C.F.R. Section 1.1307, such that it osure of workers or the general public ty guidelines issued by the American	Yes No
If you answer Yes, Section 1.1311.	submit as an Exhibit an Environmenta	l Assessment required by 47 C.F.R.	Exhibit No.
If No, explain brief	· , · · · · , · · · · ·	-3, measurements will IFICATION	be taken.
	pared this Section of this application on bate and true to the best of my knowledge	ehalf of the applicant, and that after s	uch preparation, I have examine
Name (Typed or Printed		Relationship to Applicant (e.g.,	Consulting Engineer)
John J. M	ullaney	Consulting Eng	
Signature	[[malloney	Address (include ZIP Code)Mu 9049 Shady Gro Gaithersburg,	

Telephone No. (include Area Code)

301-921-0115

DECLARATION

I, John J. Mullaney, declare and state that I am a graduate electrical engineer with a B.E.E. and my qualifications are known to the Federal Communications Commission, and that I am an engineer in the firm of Mullaney Engineering, Inc., and that firm has been retained by Dogwood Communications, Inc., licensee of Radio Station WAMJ at Roswell, Georgia, to prepare an application for a "one-step" upgrade.

All facts contained herein are true of my own knowledge except where stated to be on information or belief, and as to those facts, I believe them to be true. I declare under penalty of perjury that the foregoing is true and correct.

John J. Mullaney

Executed on the 5th day of March 1998.

ENGINEERING EXHIBIT EE-3:

RADIO STATION WAMJ
DOGWOOD COMMUNICATIONS, INC.
ROSWELL, GEORGIA
Ch. 298C3 9.2 KW-DA 163 M HAAT

NARRATIVE STATEMENT:

I. GENERAL:

This engineering statement has been prepared on behalf of Dogwood Communications, Inc., licensee of Radio Station WAMJ at Roswell, Georgia. The purpose of this statement is to request a Construction Permit authorizing a "one-step" upgrade from Channel 298A to 298C3. WAMJ proposes to change sites and operate with an ERP of 9.2 KW-DA and an HAAT of 163 Meters. This application proposes facilities which are in compliance with the contour protection requirements of Section 73.215. As will be shown herein, there is a special reference point which meets all of the minimum separations required for C3 operation.

This upgrade was made possible with the deletion of Ch. 298A at La Fayette, Georgia (MM Docket 97-196, effective date: 3/9/98). This upgrade application is mutually exclusive with a pending rule making by Radio Station WPEZ to re-allot FM Ch. 300C1 from Macon to Hampton, GA (MM Docket 98-18, comment date: 4/13/98).

This upgrade application is \underline{not} a major environmental action, as defined by Section 1.1307 of the Commission's Rules. The

RADIO STATION WAMJ - C3 UPGRADE Ch. 298C3 - ROSWELL, GA (3/98)

MULLANEY ENGINEERING, INC.

proposed facility is in full compliance with both the "controlled" & "un-controlled" FCC Radiation Guidelines.

Answers to questions contained in F.C.C. Form 301, Section V-B, are incorporated in the following paragraphs and figures.

II. ENGINEERING DISCUSSION:

A. Proposed Location:

WAMJ proposes to locate at an existing communication site atop a building at 3340 Peachtree Road, Atlanta, GA. Thus a topographic map showing the proposed site is not required. The geographic coordinates are:

Latitude: 33° 50′ 48″ Longitude: 84° 22′ 16″

The city of license, Roswell, Georgia, is located approximately 19.5 kilometers north of the proposed site. The Regional Office of the FAA was <u>not</u> notified of this proposal since the existing height of the support structure will not change.

B. Antenna System and Tower:

A dual polarized 4-bay half wave spaced FM antenna will be side mounted on a tower atop an existing building. Figure 3 is a sketch of the proposed tower. The antenna has a directional power gain of 1.4 H/V.

Figure 6 is a polar plot of the relative horizontal field pattern. Figure 6-A is a tabulation of the proposed pattern in relative field, DBK and KW. The antenna will be mounted in accordance with recommendations from the directional antenna manufacturer. In addition, no top mounted platforms or other antennas will exist in close

RADIO STATION WAMJ - C3 UPGRADE Ch. 298C3 - ROSWELL, GA (3/98)

MULLANEY ENGINEERING, INC.

proximity of the FM antenna unless approved by the antenna manufacturer.

The antenna will be fed by 30.5 Meters (100 Feet) of 1-5/8" coaxial cable, with a rated efficiency of 94.8 percent for this length.

C. Transmitter:

WAMJ plans to install a type accepted 8 KW FM transmitter. The transmitter will be operated at 6.93 KW which is within its rated power.

D. Effective Radiated Power:

Giving consideration for the maximum antenna gain, transmitter power and line loss, the maximum Effective Radiated Power is 9.2 KW-DA for the Horizontal and 9.2 KW for the Vertical Component.

A Class-C3 FM station is restricted to a maximum of 25 KW (ERP) up to a maximum Height Above Average Terrain (HAAT) of 100 Meters. This proposal will operate with an HAAT that exceeds the maximum and consequently must reduce its ERP in order to obtain equivalent coverage within the 1.0 mV/M contour.

Current F.C.C. policy permits stations that are beyond 320 kilometers from the Mexican or Canadian Borders to use the F(50,50) curves to determine what reduced power at their HAAT will provide the equivalent maximum $1.0 \, \text{mV/M}$ coverage allowed.

Using the curve, it was determined that 9.2 KW at an HAAT of 163 Meters is equivalent to the maximum normally allowed.

E. Channel Allocation:

Figure 4 is a channel allocation study from the proposed The proposed site is short spaced under the C3 site. rules to two stations. The first short spacing 10.1 km is to WCGQ on 297C at Columbus, GA. Protection to WCGQ will be provided in accordance with Section 73.215. The second short spacing of 10.4 km is to a pending rule making to re-allot FM Ch. 300Cl from Macon to Hampton, GA (MM Docket 98-18, comment date: 4/13/98). Inasmuch as Section 73.215 limits the maximum short spacing between a C3/C1 two channels apart to 1 km, this C3 upgrade application is "mutually exclusive" with the proposed rule making.

In all other respects this application is in compliance with Section 73.207(a).

1. Contour Protection - Section 73.215:

Figure 5 is a "white-paper" map and Figure 5-A is a tabulation of the protected 60 dBu and the first adjacent interfering 54 dBu contour proposed by this application.

Figure 5-B is a similar tabulations for WCGQ except that it is based upon maximum permissible ERP and HAAT at their existing site.

As can be seen, through the use of a directional antenna system, no prohibited overlap occurs. All contours are based upon terrain radials spaced every 5 degrees.

F. "One-Step" Special Reference Point:

Figure 8 is a C3 channel allocation study from a hypothetical special reference point some 3.5 km south of downtown Roswell, GA. The geographic coordinates are:

Latitude: 33° 59′ 11" Longitude: 84° 21′ 06"

Figure 8-A is a topographic map showing the hypothetical special reference point. As can be seen, the selected reference point is the same location of a communications tower so as to conclusively demonstrate that construction is feasible.

G. Terrain Profile Data & Coverage:

Terrain profile data was extracted from NGDC 30 Second Digitized Terrain Data Base provided out of Boulder, Colorado. At least twenty-four bearings (every 15 degrees) were used to obtain the proposed coverage data. The standard eight bearings (every 45 degrees) were used to obtain the proposed HAAT.

The predicted service contours, as shown in Figure 2 of the attached report, were computed using a mathematical model adapted for computer use of the data shown in Figure 1 of Section 73.333. This is the Commission's computer program TV FM FS REPORT RS-76-01, dated January 1976.

The coverage map (Figure 2) does contain the original latitude and longitude markings as required by the FCC form 301. However, it was impossible to show the original degree indications for these markings due to the scale of the map being used (1:500,000).

Figure 2-A is a tabulation of the distances to the 70 dBu (3.16 mV/M - City Grade) & 60 dBu (1.0 mV/M - Primary) contours in Metric Units (Meters/Kilometers).

H. Terrain Profile to City of License:

The N-0-E radial is the direct path to the City of License. From the proposed site the 3.16 mV/M City Grade Contour will completely encompass the City of License without major terrain obstruction. Figure 2-B is a 1:250,000 map showing the proposed 70 dBu coverage to the city of license, Roswell, GA.

I. Coverage Area and Population:

The area contained within the 60 dbu (1.0 mV/m) contour has been computed mathematically.

The population within this contour was obtained through a computerized analysis of the census designated places population data contained in the 1990 Census.

J. FM Blanketing Contour:

WAMJ recognizes its obligation to resolve related interference complaints for a one year period within its 115 dBu "FM Blanketing Contour" as required by Section 73.318 of the FCC Rules.

Given that a half wave spaced antenna will be used, no problems are anticipated.

K. Other Services in Area:

There are NO known AM Broadcast Stations within 3.2 kilometers of the proposed site.

This is a existing electronic site. Besides what already exists at the site there are no known transmission

facilities within 60 meters (197 feet) of the proposed antenna.

There are other FM and TV transmitters within 10 km (6.2 miles) of the proposed site, however, based on the type of transmitter proposed, and the frequency & power involved no intermodulation interference problems with existing transmitting facilities is expected. In the unlikely event some problems would occur, WAMJ will investigate and correct such cases in accordance with the Commission's Rules.

L. Environmental Assessment Statement:

WAMJ believes its proposal will <u>not</u> significantly affect the environment since it does not meet any of the criteria specified in Section 1.1307 of the rules. Since an existing building will be used with no change in overall height the only remaining environmental issue is R.F. Exposure. Specifically the proposed facility:

1. Will <u>NOT</u> involve the exposure of workers or the general public to levels of radiofrequency radiation in excess of the guidelines recommended by the FCC - OET Bulletin 65 (August 25, 1997).

The following is a more detailed discussion of this protection standard:

a. National Environmental Policy Act of 1969:

In 1969, Congress enacted the National Environmental Policy Act (NEPA), which requires the FCC to evaluate the potential environmental significance of the facilities it regulates and authorizes. Human exposure to Radio Frequency (RF) radiation has been identified as an issue

RADIO STATION WAMJ - C3 UPGRADE Ch. 298C3 - ROSWELL, GA (3/98)

MULLANEY ENGINEERING, INC.

the FCC must consider.

Beginning with the filing of applications after January 1, 1986, broadcast stations "certify compliance" with FCC required to prescribed guidelines on human exposure to RF The FCC standard was based upon the radiation. American National Standards Institute's (ANSI) (ANSI radiation protection quides limits C95.1-1982). These exposure are expressed in terms of milli-watts per square centimeter.

In October 1997, the FCC implemented a two tier evaluation criteria utilizing recommendations of the National Council on Radiation Protection and Measurement (NCRP). The "controlled" tier involves areas which have restricted access while the "un-controlled" tier involves areas which have unrestricted access. The Maximum Permissible limits for (MPE) Exposure "controlled" areas are the same as adopted in 1985 while the "un-controlled" limits for FM and TV frequencies are one-fifth or 20% of the limits for "controlled" areas.

These exposure limits are time-averaged over any six minute period and vary depending upon the frequency involved. The following are the Maximum Permissible Exposure (MPE) limits for "controlled" areas:

_	(MI	cy Range Hz) ******	Power Density (mW/sq.cm) *****				
0.3	to	3	100	AM			
3	to	30	900/(Freq ²)				
30	to	300	1.0	VHF	TV	&	FM
300	to	1,500	Freq/300	UHF	TV		
1500	to	100,000	5.0				

WAMJ recognizes that compliance with the above criteria at sites involving multiple AM, FM and/or TV facilities is based upon the contributions of all such facilities. At the site discussed in this application, the only significant facility that will exist is the proposed FM facility.

However, because of the <u>numerous</u> other communications facilities on the roof top, WAMJ herein <u>commits</u> to take RF Exposure measurements to document that the site is in compliance <u>prior</u> to commencing Program Test Authority (PTA) for its upgraded C3 facility. The remaining part of the RF Exposure analysis contained herein will be limited to the proposed C3 FM.

FM BROADCAST STATIONS

For FM Broadcast Stations the following formula is used:

$$D = \frac{SQRT(F^2 * [HERP + VERP])}{1.667 * SQRT(PD) * 3.2808}$$

Where:

F = typical relative field factor in downward direction (F = 1 is worst case main lobe)

HERP = Horizontal ERP in watts (above a dipole)
VERP = Vertical ERP in watts (above a dipole)

PD = highest Power Density in milli-watts/cm²

SQRT = Square Root

Freq = Frequency in mega-cycles/sec. (mHz)

The vertical radiation pattern of the FM antenna specified in this application is very narrow and, therefore, the power density as seen by an observer on the ground near the base of the tower will be less than 10 percent of the total ERP.

The application of the above equation (assuming maximum ERP), in our case, for a frequency of 107.5 MHz and a "un-controlled" Power Density 0.2 milli-watts results in a distance of 55.5 meters (182 feet) from antenna. Inasmuch as the lowest element on the will approximately proposed antenna be (65 feet) roof 19.8 meters above level, additional analysis is required before one can conclude that no hazard will exist.

Figure 7 is a vertical elevation plot for an ERI 4 bay half-wave spaced FM antenna (LPX-4AC-HW).

Figure 7-A is a plot of the predicted RF Exposure at 7 feet above roof level. The "solid" line assumes a vertical form factor of F=1.0 while the "dashed" line uses the vertical form factor from Figure 7. As can

RADIO STATION WAMJ - C3 UPGRADE Ch. 298C3 - ROSWELL, GA (3/98)

MULLANEY ENGINEERING, INC.

be seen, the use of the 4 bay half-wave spaced FM antenna reduced the exposure at roof level (within a radius of 500 feet) below 49.7 uW/sg.cm or 4.97%percent of the standard for a "controlled" area. the "un-controlled" standard is 20% and, therefore. this proposal is in full compliance. Because of the complexities of a roof top site, WAMJ is committing herein Exposure take RF measurements document that the site is in compliance prior to commencing Program Test Authority (PTA) for its upgraded C3 facility.

The door to the roof will be locked to limit access.

Workers employed to climb the tower or work in a potential over-exposure location will not be permitted to enter the work area until cleared by the station manager or other responsible person. Appropriate warning signs will In addition, WAMJ posted to insure safety. establish and enforce work rules safety procedures applicable in a potential over-exposure area. The rules will establish how close a worker can get to the antenna when it is operating at normal power and specify the power reduction required in order to make other locations safe. Ιt is recognized maintenance or installation work on or near the antenna may require the station to completely shutdown or switch temporarily to an auxiliary antenna or an auxiliary transmitter site. employees, contract and other persons having access to areas of potential exposure will be

required to sign a site management guide indicating they are aware of and will comply with <u>all</u> safety rules. In the instance of a multiple use site, a single site access policy incorporating the above philosophy will be established. All procedures will be reviewed & updated as necessary.


III. SUMMARY:

Dogwood Communications, Inc., licensee of Radio Station WAMJ at Roswell, Georgia, requests a Construction Permit authorizing a "one-step" upgrade from Channel 298A to 298C3. WAMJ proposes to change sites and operate with an ERP of 9.2 kW-DA and an HAAT of 163 Meters. This application proposes facilities which are in compliance with the contour protection requirements of Section 73.215. As will be shown herein, there is a special reference point which meets all of the minimum separations required for C3 operation.

This upgrade was made possible with the deletion of Ch. 298A at La Fayette, Georgia (MM Docket 97-196, effective date: 3/9/98). This upgrade application is mutually exclusive with a pending rule making by Radio Station WPEZ to re-allot FM Ch. 300C1 from Macon to Hampton, GA (MM Docket 98-18, comment date: 4/13/98).

This engineering proposal is in full compliance with the Commission's Rules.

Il I mullanez



FM COVERAGE *******

WAMJ C3 UPGRADE - FROM TOWER PLACE

3/98

CHANNEL NO. 298 C3 FREQUENCY 107.5 MHZ CENTER OF RADIATION 448.1 METERS AMSL COORDINATES: 33-50-48 / 84-22-16

MAXIMUM ERP 9.2 KW-DA

			2 16 ****				STANCE !	
	BEARING		3-16 KM		E.R.P.		rours (1	
	*****		AVERAGE		(KW) ******		/U.U t*****	60.0
	~~~~~	-	******	*****	*****	*****		
CITY	0.	*	295.3	152.8	9.200	1.2	22.4	38.0
	15.		303.8	144.3		1.2	21.7	
	30.		292.5	155.6		1.2	22.5	38.3
	45.	*	299.8	148.3	9.200	1.2	22.0	37.3
	60.		294.0	154.1		1.2	22.4	38.0
	75.		282.8	165.3	9.200	1.2	23.2	39.3
	90.	*	294.6	153.5	9.200	1.2	22.4	38.0
	105.		294.8	153.3	9.200	1.2	22.4	38.0
	120.		285.5	162.6	9.200	1.2	23.0	38.9
	135.	*		159.7		1.2	22.9	38.6
	150.		285.8		9.200	1.2		38.9
	165.		286.2		8.200	1.1	22.4	38.0
	180.	*	285.0		4.303	0.8		32.8
	195.		287.4	160.7		0.7	17.5	29.9
	210.		280.6		2.715	0.6		29.8
	225.	*		181.4		0.7	19.0	
	240.		251.3		6.220	1.0	22.9	38.9
	255.		250.6	197.5		1.2	25.1	42.2
	270.	*	269.1	179.0		1.2	24.0	40.7
	285.		287.9	160.2		1.2	22.9	38.8
	300.		285.3	162.8		1.2	23.0	39.1
	315.	*	400.1	162.7		1.2	23.0	39.1
	330.		287.0	161.1		1.2	22.9	38.8
	345.		301.4	146.7	9.200	1.2	21.9	37.2
AVERA	GE ( 8)	*	285.5	162.6	Meters			

**AVERAGE** (8) * 285.5 162.6 Meters

AREA IN SQUARE KILOMETERS 3.83 1511. 4352.

115.0 DBU BLANKET CONTOUR IS COMPUTED VIA SECTION 73.318

TABULATION OF PROPOSED CONTOURS

RADIO STATION WAMJ ROSWELL, GEORGIA Ch. 298C3 9.2 KW-DA 163 M HAAT MULLANEY ENGINEERING, INC. GAITHERSBURG, MARYLAND

> FIGURE 2-A MARCH 1998